# AI-Track-tive: open source software for automated recognition and counting of surface semi-tracks using

computer vision (Artificial Intelligence)

Simon Nachtergaele<sup>1</sup>, Johan De Grave<sup>1</sup>

<sup>1</sup>-Laboratory for Mineralogy and Petrology, Department of Geology, Ghent University, Ghent, 9000, Belgium

Correspondence to: Simon Nachtergaele (Simon.Nachtergaele@UGent.be)

# Abstract

5

Artificial intelligence techniques such as deep neural networks and computer vision have been trained to detect fission surface semi-tracks. The deep neural networks can be used in an open source computer program for semi-automated fission track dating called "AI-Track-tive". Our custom-trained deep neural networks use YOLOV3 object detection algorithm, which is

10 currently one of the most powerful and fastest object recognition algorithms. The developed program successfully finds most of the fission tracks in the microscope images, however, the user still needs to supervise the automatic counting. The presented deep neural networks have high precision for apatite (97%) and mica (98%). Recall values are lower for apatite (86%) than for mica (91%).

# Introduction

- 15 Fission track dating is a low-temperature thermochronological dating technique applicable on several minerals (mainly apatite and zircon) and glass, and was first described in detail by Fleischer et al. (1975). Since the discovery of the potential of apatite fission track dating for reconstructing thermal histories (e.g. Gleadow et al., 1986; Green et al., 1986; Wagner, 1981), apatite fission track dating has been utilized in order to reconstruct thermal histories of basement rocks and apatite-bearing sedimentary rocks (e.g. Malusà and Fitzgerald (2019); Wagner and Van den haute, (1992)). As of 2020, more than 200 20 scientific papers with apatite fission track dating results are published every year. Hence, apatite fission track dating currently
- is a widely applied technique in tectonic and other studies.

Fission track dating techniques are labour-intensive and are highly dependent on accurate semi-track recognition using optical microscopy. Automation of the track identification process and counting could decrease the analysis time and increase reproducibility. Several attempts have been undertaken in order to develop automatic counting techniques (Belloni et al., 2000;

- 25 Gold et al., 1984; Kumar, 2015; Petford et al., 1993). The Melbourne Thermochronology Group in collaboration with Autoscan Systems Pty was the first to provide an automatic fission track counting system in combination with Zeiss microscopes. The currently only available automatic fission track recognition software package is called FastTracks. It is based on the patented technology of "coincidence mapping" (Gleadow et al., 2009). This procedure includes capturing microscopy images with both reflected and transmitted light. After applying a threshold to both images, a binary image is obtained. Fission tracks are 30
  - automatically recognized where the binary image of the transmitted light source and reflected light source coincide (Gleadow

1

Verwijderd: has been the Technical note: Verwijderd: fission track recognition

-{	Verwijderd: developed
-{	Verwijderd: for
-	Verwijderd: recognition
1	Verwijderd: and included
Y	Verwijderd:
ľ	Verwijderd: for the first time
Y,	Verwijderd: These
ľ,	Verwijderd: the
ľ,	Verwijderd: Yolo
Ì	Verwijderd: These deep neural networks can be used in new software called "AI-Track-tive".
ľ	Verwijderd: The success rates of the
	Verwijderd: automatic recognition range from 70% to 100% depending on the areal track densities in apatite and (muscovite) external detector. The success rate generally decreases for images with high areal track densities, because overlapping tracks are less easily recognizable for computer vision techniques.
Y	Verwijderd: geochronological
Y	Verwijderd: developed
1	Verwijderd: Anno

Verwijderd: and consequent track counting

Verwijderd: most successful attempt by the

55 et al., 2009). Recently, potential improvements for discriminating overlapping fission tracks were also proposed (de Siqueira et al., 2019).

Despite promising initial tests and agreement between the manually and automatically counted fission track samples reported in Gleadow et al. (2009), challenges remain for the track detection strategy (Enkelmann et al., 2012). The automatic track detection technique from Gleadow et al. (2009) incorporated in <u>earlier versions of FastTracks</u> (Autoscan) did not work well in

- 60 the case of (1) internal reflections (Gleadow et al., 2009), (2) surface relief (Gleadow et al., 2009), (3) over- or underexposed images (Gleadow et al., 2009), (4) shallow-dipping tracks (Gleadow et al., 2009) and (5) very short tracks with very short tails. More complex tests of the automatic counting software (FastTracks) undertaken by two analysts from University of Tubingen (Germany) showed that automatic counting without manually reviewing leads to severely inaccurate and dispersed counting results which are less time-efficient than manual counting using the "sandwich technique" (Enkelmann et al., 2012). However,
- 65 the inventors continuously developed the system and solved the aforementioned problems. This has resulted in fission track software that is acquired by most of the fission-track labs and it is generally assumed as the one and only golden standard for fission-track dating.

This paper presents a <u>completely</u> new approach for automatic detection of fission tracks in both apatite and muscovite. Normally, fission tracks are detected using segmentation of the image into a binary image (Belloni et al., 2000; Gleadow et

- 70 al., 2009; Gold et al., 1984; Petford et al., 1993). Here, in our approach, segmentation strategies are abandoned and replaced by the development of computer vision <u>(so-called Deep Neural Networks)</u> capable of detecting <u>hundreds of fission tracks in a</u> <u>1000x magnification microscope image</u>. It will be shown later in this paper that artificial intelligence techniques such as computer vision can be a solution for the labour-intensive manual counting, as already recognized by <u>the pioneering work of</u> Kumar (2015). Kumar (2015) was the first to successfully apply one machine learning technique (support vector machine) on
- 75 a dataset of high quality single (?) semi-track images (30x30μm). This paper reports results of deep neural networks that can detect one to hundreds of semi-tracks in an individual image of 117.5 μm width and 117.5 μm height. This new potential solution for apatite fission track dating is currently available as an executable program (.exe) and Python source code with the name "AI-Track-tive". The deep neural networks and the method to train a deep neural network are also available to the scientific community.

#### 80 1 Methods

#### 1.1 System requirements

AI-Track-tive uses two deep neural networks capable of detecting fission tracks in apatite and in muscovite mica. The deep neural networks have been trained on microscope images taken on 1000x magnification. Using the deep neural networks, unanalyzed images can be <u>analysed automatically</u> after which it is possible to apply manual corrections. Although it is tested on output from a Nikon Ni-E Eclipse microscope with Nikon-TRACKFlow software (Van Ranst et al., 2020), AI-Track-tive

85 on output from a Nikon <u>Ni-E Eclipse microscope with Nikon-TRACKFlow software (Van Ranst et al., 2020), AI-Track-tive is certainly platform-independent. The only required input for <u>AI-Track-tive</u> are .jpg <u>microscopy</u> images from both transmitted</u>

Verwijderd: oes

-{	Verwijderd: the
-	Verwijderd: the
-1	Verwijderd: mineral

**Verwijderd:** Below, it will be shown that a custom-trained deep neural network can detect almost all tracks in apatite and muscovite external detectors.

Verwijderd: for apatite and mica

λ	Verwijderd: custom-trained
λ	Verwijderd: based on
λ	Verwijderd: training data of high-quality output
-	Verwijderd: these
1	Verwijderd: analyzed
-	Verwijderd: automatically
-(	Verwijderd: system
λ	Verwijderd: ¶

and reflected light with an appropriate size (e.g. 1608x1608px or 804x804px), AI-Track-tive contains a Graphical User Interface (GUI) from which it is easy to choose the appropriate analysis settings and the specific images. The only requirements to train a custom-made DNN is a good internet connection and a Google account. For Windows users it is possible to download, subsequently open the folder and execute the .exe file from which the AI-Track-tive program will open. For Apple and Linux

 105
 subsequently open the folder and execute the .exe file from which the AI-Track-tive program will open. For Apple and Linux users, it is necessary to install some freeware Spyder IDE, Python 3.8 and some specific Python modules (OpenCV and PyQt)

 before they can run the program. The executable file, Python source code, DNN's and specific instructions can be downloaded ("cloned") on the code repository https://github.com/SimonNachtergaele .

# 1.2 Development

- 110 The software makes use of a self-trained deep neural network based on the Darknet-53 backbone (Redmon and Farhadi, 2018) which has become extremely popular in object recognition for all kinds of purposes. The Darknet-53 backbone in combination with YOLOv3 head configuration can be combined and trained to be used as an automatic object detection tool. This deep neural network can be trained to recognize multiple classes, for example cats or dogs. The deep neural network presented in this paper is trained on only one class. i.e. etched semi-tracks. Two deep neural networks were trained specifically for semi-
- 115 tracks in apatite and in mica. They were both trained on <u>a manually annotated dataset of 50</u> images for apatite and <u>50</u> images for mica, AI-Track-tive has been developed in Python v3.8 (Van Rossum and Drake Jr, 1995) using several Python modules, such as <u>an open source computer vision module called OpenCV (Bradski, 2000). The GUI is constructed using Tkinter (Lundh, 1999). The easy-to-handle GUI with multiple interactive windows should make it possible to use the platform on any computer without knowledge of Python programming language (Figure 1).</u>

# 120 <u>1.2.1 Sample preparation</u>

125

130

In order to create suitable images for DNN training, we converted the z-stacks .nd2 files acquired by Nikon Ni-E Eclipse microscope to single-image .tiff images of 1608 pixels by 1608 pixels using the Nikon Advanced Research software package. It is assumed that the microscopy software rotates and horizontally flips the mica images before exporting to .tiff files. Subsequently, we converted these images to "smaller" .jpg format using freeware Fiji (Schindelin et al., 2012). In Fiji we converted the .tiff images to .jpg using no compression, resulting in 1608px on 1608px images (2.59 MP). We then also

implemented a 0.5 factor compression which resulted in smaller 804px on 804px .jpg images (0.64 MP).

#### 1.2.2 Deep Neural Networks: introduction

Our Deep Neural Network (DNN) consists of two parts: a "backbone" combined with a "head" which detects the class and object of interest. As mentioned, we opted for a Darknet-53 backbone (Redmon and Farhadi, 2018) combined with a YOLOV3 head (Redmon and Farhadi, 2018). The Darknet-53 backbone consists of 53 convolutional layers and some residual layers in between (Redmon and Farhadi, 2018). The Darknet-53 backbone in combination with a YOLOV3 "head" can be trained so that it recognizes an object of choice. The training process is a computer-power demanding process requiring the force of high-

-{	Verwijderd: for example
$\neg$	Verwijderd: )
Ľ	Verwijderd: g
Ľ	Verwijderd: u
$\langle \rangle$	Verwijderd: i
Y	Verwijderd: the specific images and

Verwijderd: This program utilizes a
Verwijderd: fission track recognition
Verwijderd: (Darknet
Verwijderd: )
Verwijderd: from the Yolov3 object detection algorithm (Redmon and Farhadi, 2018).
Verwijderd: This deep neural network is used as an
Verwijderd: which can be trained for several objects.
Verwijderd: "
Verwijderd: "
Verwijderd: (
Verwijderd: )
Verwijderd: 15
Verwijderd: 25
Verwijderd: on 1000x magnification
Verwijderd: and

155 end GPU's that would take several days on normal computers. In order to shorten this training process, it is possible to use powerful GPU units from Google Colab. Using the hosted runtime from Google, it is possible to use the available high-end GPU's for several hours while executing a Jupyter Notebook. While many other alternatives are available, we chose for YOLOv3 with Darknet-53 pre-trained model, because it is one of

the fastest and most accurate convolutional neural networks (Redmon and Farhadi, 2018) at the time of developing this software. With YOLOv3 it is possible to perform real-life object detection using a live camera or live computer screen

160 software. With YOLOv3 it is possible to perform real-life object detection using a live camera or live computer screeen (Redmon and Farhadi, 2018). From a geologist's perspective it seems that Artificial Intelligence's object detection is a very rapidly evolving field in which several new DNN configurations are created every year (e.g. YOLOv4 in 2020). The chances are high that the presented YOLOv3 DNN could already be outdated in some years. Therefore, we will provide all necessary steps to train a DNN which could potentially be more efficient than our current DNN. For these future DNN's it should be possible to use AI-Track-tive in which DNN's can be utilized other than YOLO. OpenCV 4.5 can handle other DNN's than YOLO such as Caffe (Jia et al., 2014), Google's TensorFlow (Abadi et al., 2016), Facebook's Torch (Collobert et al., 2002).

DLDT Openvino (https://software.intel.com/openvino-toolkit) and ONNX (https://onnx.ai/).

1.2.3 Deep Neural Networks: training and configuration

- DNN training includes two steps. The first step includes annotating images with LabelImg (https://github.com/tzutalin/labelImg) or AI-Track-tive. These training images were each square-sized images with a width and height of 117.5µm taken with a Nikon Ni-E Eclipse optical light microscope on 1000x magnification. This first step includes manually drawing thousands of rectangles covering every semi-track. It is advisable to train the DNN on a difficult dataset in which (1) several tracks are overlapping with one another, (2) light exposure varies, (3) images are slightly out- and in-focus. For apatite, we drew a total of 4734 rectangles indicating 4734 semi-tracks in 50 images. For mica, a total of 6212
- 175semi-tracks were added in 50 images. The arithmetic mean of track densities was in this case  $7.9 \times 10^5 \frac{tracks}{cm^2}$  (Figure 2).The second step is executing a Jupyter notebook and connecting it to Google Colab (<a href="https://colab.research.google.com">https://colab.research.google.com</a>).Google Colab is a free platform where one can execute their Python code using Google's Graphical Processing Unit (GPU)resources. This gives the possibility to train a DNN in a few hours using much more GPU power than normally available.Google Colab provides a maximum of 8 hours of working time using very powerful (but expensive) GPU's such as Nvidia
- Tesla K80, T4, P4 or P100. These GPU's are utilized to adapt the Darknet53 (.weights) file to the training dataset using a configuration file (.cfg) through an iterative training process during which it will progressively recognize the tracks better. This iterative training process creates for every 100 iterations a new .weights file. The "average loss" is a value that expresses the accuracy of track recognition of the trained .weights file. This average loss value is high in the beginning of the training process (~10<sup>3</sup>) but decreases to <10 after a few hours of training. The speed of the iterative training process depends on many factors that are specified in the YOLOv3 head. It is possible to change the training process by adapting the configuration of the YOLOv3 head in the .cfg file. In the .cfg file, several configuration parameters of the DNN are specified such as for</li>

example the learning rate and network size. The network size is in our case was  $416 \times 416$ , implying that it will resize our images of  $804 \times 804$  to  $416 \times 416$ . We experienced that increasing the network size from  $416 \times 416$  to  $608 \times 608$  or increasing image size from  $804 \times 804$  px to  $1608 \times 1608$  px strongly decreases the iteration speed. Hence, we chose to train a DNN with  $416 \times 416$  network size using pictures of  $804 \times 804$  px.

#### 1.2.4 Deep Neural Networks: testing

The efficiency of every trained DNN can be tested using images ("test images") that are not part of the training dataset. When YOLOv3 configuration is used to find the object of interest (semi-tracks), it predicts a high number of bounding boxes with each a different place, width, height and confidence value in the image. The confidence value is normally high (>95%) for the

 easy recognisable tracks and rather low for the less obvious semi-tracks, as illustrated in Figure 3. <u>A user-defined threshold</u> value defines the threshold value (e.g. 50%) above which rectangles are drawn on test image.
 For one semi-track, YOLOv3 predicts several overlapping bounding boxes (Redmon et al., 2016). Therefore, an essential non-

maximum suppression step leads to one rectangle surrounding the semi-track. In the often occurring scenario that several semitracks coincide or overlap, it is highly likely that only one rectangle is drawn after a conservative non-maximum suppression

200 filtering. AI-Track-tive sometimes struggles with identifying multiple tracks even though we adapted the "nms\_treshold" value in order to allow the drawing of multiple boxes for coinciding tracks.

# 2 Results

190

# 2.1 AI-Track-tive: new software for semi-automatic fission track dating,

The result of the unique strategy for automated fission track identification is embedded in the "AI-Track-tive" program. It is an interactive program useful for analysing several types of samples, such as (1) an apatite and external detector couple, (2) <u>an external detector (mica) covering a</u> Uranium-doped glass, and (3) <u>only apatite (Figure 1)</u>, e.g. for LAFT analysis. The user can import <u>one or two transmitted light images with different z-level</u> in AI-Track-tive <u>from which it will create a blended</u> <u>image through which the focal level can be changed manually</u>. This way, the analyst gets a 3D impression of the image containing the tracks. The user also needs to import reflected light images from which it is possible to change rapidly using

210 the computer mouse wheel function. The user can optionally choose for a region of interest in which the fission tracks will be sought. The user can choose between, a square-shaped 100µm by 100µm grids, a user-defined polygonal, or a <u>user-defined</u> circular window with an adaptable diameter, (Figure 1). Due to the very rapid <u>YOLO</u>v3 algorithm (Redmon et al., 2016; Redmon and Farhadi, 2018), it is possible

to instantaneously detect the semi-tracks in the loaded images. The result of the track recognition is an image in which every detected fission track is indicated with a rectangle <u>comprising the detected fission track</u>. Every rectangle located <u>with more</u> than half <u>of</u> its surface inside the polygon (or region of interest) is counted. Each track has a certain confidence score, as illustrated on Figure 3. This confidence score is close to 1 for easily recognisable tracks and much lower for overlapping tracks. Verwijderd: : a new program for automated fission track counting

Verwijderd:	-covering 1	mica
-------------	-------------	------

Verwijderd:	a split z-stack
-------------	-----------------

Verwijderd: after which it will automatically find the best focussed image for both apatite and its external detector

1	Verwijderd:
-(	Verwijderd: either choose
4	Verwijderd: for
-{	Verwijderd: in which AI-Track-tive will search for tracks
1	Verwijderd: Yolo
	Verwijderd: automatic track recognition is performed almost instantaneously.
4	Verwijderd: for
λ	Verwijderd: ¶

This confidence score is shown on Figure 3 for illustration, <u>but normally it is not displayed</u>. <u>Currently, track detection is not</u> 100% successful for every image. Therefore, manually reviewing is <u>absolutely necessary and essential to obtain useful data</u>. While reviewing the track detection results, it is possible to switch between reflected and transmitted light images by scrolling

235 the computer mouse wheel. Unidentified semi-tracks can be manually added and mistakenly added tracks can be removed using the computer mouse buttons following the instructions written in the instructions window. These manual corrections will be displayed immediately in a different colour on the microscope image.

The adjusted image is saved as a .png file after the manual revision process is completed, Track counting results are exported in .csv files together with all useful information. Hence, performing your own zeta-calibration (Hurford and Green, 1983) or GQR calibration (Jonckheere, 2003) is possible.

#### 2.1.1 AI-Track-tive: live fission track recognition

240

255

Due to the accurate and fast nature of the YOLOv3 object detection algorithm, it is possible to do real-time object detection (Redmon and Farhadi, 2018). In AI-Track-tive it is possible to let a DNN detect fission tracks on live images from your computer screen. The only drawback for the "live fission track recognition" is the computer processing time of approximately

0.3 to 0.5 seconds, depending on the hardware of the computer system. Real-time object detecting neural networks are much more useful in environments in which the detected objects are dynamic. Obviously, etched semi-tracks are static, so it is not so helpful to detect fission tracks on live images. The usefulness of this "live recognition" function might be twofold. The first application lies in the fast evaluation of the trained Deep Neural Networks. The second application relates to an implementation into microscope software. "Smart" microscopes using live semi-track track recognition could distinguish apatite (containing semi-tracks) from other minerals which are in between the apatite grains.

# 2.1.2 AI-Track-tive: DNN training

It is possible to use AI-Track-tive to construct a training dataset for further DNN training based on a custom dataset. This training dataset can be created by loading images in AI-Track-tive and highlighting the tracks manually. This way, an unexperienced programmer potentially uses this software instead of other dedicated (and more widely-tested) software (LabelImg) to create a training dataset comprising images (.jpg) and accompanying annotations (.txt) files. In AI-Track-tive it

is also possible to use AI assistance when creating training images, although this is not recommended because of the possibility

#### 2.1.3 AI-Track-tive: etch pit diameter size (Dpar) measurement

of copying the AI's mistakenly identified semi-tracks.

AI-Track-tive also has the possibility to determine the D<sub>par</sub> value (Donelick, 1993) which is the size of the semi-track's etch
 pits measured in the c-axis direction (Figure 4). For this step, AI-Track-tive does not use DNN's (yet) but instead it uses color
 thresholding. Color thresholding is the most used technique used for image segmentation. This color thresholding is sensitive
 to unequal light exposure, but this is solved by a gamma correction. AI-Track-tive filters the D<sub>par</sub> values using a threshold

verwijaera:	
Verwijderd:	Т
Vousidoud	T
verwijaera:	1
Verwiiderd:	The manually
Verwijderd:	The manually
Verwijderd: Verwijderd:	The manually at the end of the manual reviewing process.
Verwijderd: Verwijderd:	The manually at the end of the manual reviewing process.

	based on minimum and maximum size of the etch pits. After the size discrimination step, AI-Track-tive uses another 2 filters
270	based on elongation factor (width-to-height ratio) and directions (or angles) of the etch pits. The threshold values for these
	filters can be changed when advancing through the Graphical User Interface.

### 2.2. Semi-track detection efficiency

A series of analyses were undertaken in order to evaluate the <u>efficiency</u> of the <u>semi-track</u> track identification in apatite and <u>mica</u> samples with varying areal fission track densities were analysed, <u>The efficiency tests are</u> performed on 50 mica and 50 apatite images that were not included in the training dataset for the DNN development (Figure 5). For almost all images we opted to use a 100µm by 100µm square-shaped region of interest with tens or even hundreds of tracks in the image. Apatite grains with varying Uranium zoning and spontaneous track densities were analysed, The results *j* of these experiments are listed in Table 1 (apatite) and Table 2 (mica). Widely used metrics for evaluating object recognition success are calculated using the correctly recognized semi-tracks (True Positives or TP), unrecognized semi-tracks (False Negatives or FN) and mistakenly recognized semi-tracks (False Positives or FP). Typical metrics to evaluate the performance

of object detection software are precision  $\left(\frac{TP}{TP+FP}\right)$  and recall or true positivity rate  $\left(\frac{TP}{TP+FN}\right)$ .

# 2.2.1 Apatite

285

For apatite, the arithmetic mean of the precision equals 97% and for recall it is 86%. The precision is very high and indicates that very few false positives are found. Only for very low track densities it occurs that precision is lower than 0.8, probably because a few false positives have a relatively high impact in an image where only 20 tracks are supposed to be recognized. The true positivity rate (=recall) value is 86% and lower compared to the average precision. Despite the overall high scores for recall (Figure 5), it sometimes occurs that recall is lower than 0.8. Hence, it is essential that the unrecognized tracks (false negatives) are manually added.

#### 2.2.2 External detector,

290 For muscovite, the arithmetic mean of the precision equals 98% compared to 91% recall. These metrics are both higher than the ones obtained for apatite. The precision is very high indicating that false positives are scarce. Recall is above 90% and only drops below 80% for a handful of samples with low track densities (Figure 5). The frequency-histogram of the recall values and precision values are less skewed compared to the histograms of apatite (Figure 5).

# 2.3 Analysis time

295 <u>One small experiment was undertaken in which fission tracks were counted in both apatite and external detector. The results</u> of these experiments are summarized in Table 3 and compared to previous results using FastTracks reported in Enkelmann et al. (2012) and more up-to-date values of FastTracks (A. Gleadow, 2020). For our time analysis experiment, 25 coordinates in

#### Verwijderd: 2

- Verwijderd: Success rate of track recognition software
- Verwijderd: success rate

#### Verwijderd: fission

Verwijderd: for apatite (Table 1) and muscovite (Table 2).

Verwijderd: Small and large a

Verwijderd: degrees of Uranium distribution

#### Verwijderd: d

Verwijderd: Also, less transparent apatite grains with under- and overexposed parts were analysed in order to test the effect of different levels of light exposure on track recognition.

# Verwijderd: ¶

# Verwijderd: 2

Verwijderd: Fission track recognition in a

Verwijderd: ¶

Verwijderd: The track recognition results on three (100 µm on 100 µm) photos of Durango apatite can be observed in Figure 2. Panel A and B show a polygon in which fission tracks can be counted. Panel C shows the feature for using a circular counting window (useful for LAFT). In panel A of Figure 2, it can be observed that the object detection model finds most of the fission tracks. Also in panel A of Figure 2, six fission tracks were not found automatically but were also added manually (visible in yellow) using the program. These six fission tracks were not easily recognisable due to overlap with other tracks or they were located at the edge of the photo. Panel B shows an image of a lowquality apatite grain in which a custom-drawn polygonal graticule was used. Panel C shows a Durango apatite photo analyzed using a circular window of 80µm diameter. Panel A and B yield a success rate of 79% and 73%, respectively. Panel C shows an example of a success rate of 100%. Panel B and C also show that the success of the track recognition is not influenced by the brightness of the image. Based on these three examples from Figure 2 it appears that track detection success rate decreases with increasing track density.

#### Verwijderd: 2

Verwijderd: Fission track recognition in m

# Verwijderd: ica

# Verwijderd: ¶

The result of fission track recognition in mica is illustrated with one example from a mica attached to a Uranium-doped glass (Figure 3). For this image it was chosen not to use a polygon or graticule. Here, a square of 100  $\mu$ m on 100  $\mu$ m was used to determine the induced areal track density, which is the entire field of view. Figure 3 shows that 55 tracks were automatically detected (in blue) and 4 were manually [...]

-1	Verwijderd: Two
$\square$	Verwijderd: s
Y	Verwijderd: were
1	Verwijderd: ¶

a pre-annealed Durango sample (A-DUR) and its external mica detector were analysed by the first author. Selecting and imaging 25 locations in the Durango sample and its external detector took 25-35 min using <u>Nikon-</u>TRACKFlow (Van Ranst et al., 2020). Counting fission tracks in 25 locations in <u>one,pre-annealed and irradiated</u> Durango sample and its external detector (including manual reviewing) using AI-Track-tive took 30 minutes in total. It is expected that fission track counting would take some more time for samples with track densities higher than (~4 \* 10<sup>5</sup> tr/cm<sup>2</sup>)<sub>r</sub>

# 365 **3 Discussion**

380

#### 3.1 <u>Automatic semi-</u>track recognition

The success rate of automatic track recognition has been tested for several ( $\sim 50$ ) different images of apatite and external detector (mica) images. The automatic track recognition results show that the computer vision strategy is (currently) not detecting all semi-tracks in apatite (Table 1) and mica (Table 2). Hence, manual reviewing the results and indicating the "missed" track (false negatives) is essential

- 370 "missed" tracks (false negatives) is essential,
  - The precision and recall of both the apatite and mica fission track deep neural networks is compared to the areal track densities in scatter plots shown in Figure 5. The upper limit of  $10^7$  tracks/cm<sup>2</sup> was defined as the upper limit for fission track identification using optical microscopy (Wagner, 1978). The lower limit of  $10^5$  tracks/cm<sup>2</sup> was chosen arbitrarily based on the fact that apatite fission track samples in most studies have track densities within the range of  $10^5$  to  $10^7$  tracks/cm<sup>2</sup>. For track
- 375 densities lower than the arbitrarily set limit of 10<sup>5</sup> tracks/cm<sup>2</sup>, it is still possible to apply fission track analysis but it is more time-consuming with respect to sample scanning and image acquisition (i.e. finding a statistical adequate number of countable tracks in large surface areas and/or high number of individual apatite grains).

The precision and recall values discussed earlier are high and indicate that the large majority of the semi-tracks can be detected in all images. However, coinciding semi-tracks are difficult to detect for both humans and computers. Therefore, the trained deep neural networks were trained on <u>50</u> images (Table 1) in which the track densities were high and <u>the individual tracks</u>

were sometimes hard to identify due to spatial overlap (Figure 2).

3.2 Current state and outlook

With the development of AI-Track-tive it was possible to successfully introduce artificial intelligence techniques (i.e. computer vision) into fission track dating. The program presented here <u>has comparable analysis speed with other automatic fission track</u>
recognition software such as <u>FastTracks</u> from Autoscan systems (Table 3). With the current success rates of the program, we think already a significant gain is to be made. However, manually reviewing the automatic track recognition results is still (and will perhaps always be) necessary. In the near future it seems likely that computer power and artificial intelligence techniques will inevitably improve. Therefore, smarter deep neural networks with higher <u>precision and recall values</u> will likely be developed in the (near) future. <u>Although we did only work with YOLOV3 algorithms, we expect that other deep neural networks can also be used in AI-Track-tive. AI-Track-tive is an open source initiative without any commercial purpose. It is
</u>

-{	Verwijderd: a
1	Verwijderd: n
-1	Verwijderd: (Table 1)

Verwijderd: ¶	
Verwijderd: Success rate of a	
Verwijderd: 20	

Verwijderd: highly recommended
Verwijderd: success rate
Verwijderd: recognition
Verwijderd: two
Verwijderd: 4

Verwijderd: The two scatter plots of Figure 4 show that the success rate of the automated fission track recognition always remains higher than 70%. This means that the worst case scenario is that the analyst needs to manually select 30% of the fission tracks. The negative slope of the linear regression models in both panels of Figure 4 indicate that the success rate decreases exponentially with increasing areal track densities. This negative slope is observed in both scatter plots and a linear model has been fit through the data points. However, for mica the slope is quite obvious and relates to the number of coinciding semi-tracks that drastically increase with increasing track densities. C

	Verwijderd: performs
Ľ	Verwijderd: significantly faster as
Ľ	Verwijderd: red to
Y	Verwijderd: TrackWorks
-{	Verwijderd: success rates

	written in Python, a popular programming language for scientists, so that it can be continuously developed by others in the		
420	future. We would appreciate voluntarily bug reporting to the developers. Future software updates will be announced on		
	https://github.com/SimonNachtergaele	-(	Verwijderd: These new deep neural networks will be able to be used in AI-Track-tive.
	4 Conclusions	_(	Verwijderd: ¶
	In this paper we present a free method to train deep neural networks capable of detecting fission tracks using any type of		
	microscope. Secondly, we also presented open-source Python-based software called, "AI-Track-tive" on which the trained		Verwijderd: a
425	neural networks can be tested. These neural networks can be either tested on acquired images (split z-stacks) or live images	$\square$	Verwijderd: program
	coming from the microscope camera. It is possible to use AI-Track-tive for apatite fission track dating of samples and/or	Ń	Verwijderd: (
	standards. Thirdly, we provided our two deep neural networks and their training dataset which is calibrated or trained on a	X	Verwijderd: )
	Nikon Ni-E Eclipse setup.	-(	Verwijderd: that uses computer vision for conducting fission track analysis.¶
430	<ul> <li><u>unique</u> because it is, to our knowledge, the first geological dating procedure using artificial intelligence.</li> </ul>		<b>Verwijderd:</b> <#>¶ <#>innovative
	- using artificial intelligence (deep neural networks) in order to detect fission tracks automatically.	$\mathbb{N}$	Verwijderd: <#>
	- capable of successfully finding <u>almost all fission tracks in a</u> sample. The unrecognised tracks can be manually added	$\square$	Verwijderd: es
-	in an interactive window.	$\sum$	Verwijderd: and identifying 70-100
	- reliable and robust because it is not really sensitive to changes in optical settings.		Verwijderd: %
435	- future-oriented since it is software in which other, potentially smarter deep neural networks can be implemented		Verwijderd: of the
	- Python-based open source in order to give the opportunity to all scientists to improve their software for free through	\    (	Verwijderd: depending on the areal track densities of
	time	///	Verwijderd: the
	a nlatform on which system mode DNN's can be tested on live images or esthered detect	1/1	Verwijderd: fraction of
	- a platorin on which custom-made DNN's can be tested on nye mages of gathered dataset.		Verwijderd: <#>faster than the currently available fission track detection software (to our knowledge). ¶
	- potentially of use when determining the etch pit diameter (D <sub>par</sub> ).		Verwijderd: useful
440	Code availability	Č	Verwijderd:
1	All presented software can be downloaded for free on GitHub using the link: https://github.com/SimonNachtergaele		Verwijderd: The
	Video supplement Tutorial AI-Track-tive v2: https://youtu.be/CRr7B4TweHU		Verwijderd: will be made available for academic research. The only requirement is to register by sending an e-mail to Simon.Nachtergaele@UGent.be in order to obtain a password. Then, software can be downloaded for free at https://users.ugent.be/~smanacht/download.html.
	1		Verwijderd: ¶
	T		Verwijderd: https://www.youtube.com/watch?v=fSfit87vkrA&t=1

Verwijderd: ¶

# Author contribution

SN conceptualized the implementation of computer vision techniques for fission track detection and trained the deep neural networks. SN (re)wrote the software and performed all experiments described in this paper. SN made the tutorial video that can be found in video supplement. JDG acquired funding, supervised the research and reviewed the manuscript.

480

# **Competing interest**

The authors declare that they have no conflict of interest.

# Acknowledgments

SN is very grateful for the PhD scholarship received from FWO (Research Foundation Flanders). Kurt Blom is thanked for explanations on software security and helping SN out with php forms. We are indebted to Andrew Gleadow, David Chew and Raymond Donelick for their constructive comments during the review process. Pieter Vermeesch is acknowledged for excellent additional suggestions and editorial handling. We thank Sharmaine Verhaert for taking the time to test our software on a Mac-OS computer.

#### References

490 Abadi, M., Barham, P., Chen, J., Chen, Z., Davis, A., Dean, J., Devin, M., Ghemawat, S., Irving, G., Isard, M., Kudlur, M., Levenberg, J., Monga, R., Moore, S., Murray, D. G., Steiner, B., Tucker, P., Vasudevan, V., Warden, P., Wicke, M., Yu, Y. and Zheng, X.: TensorFlow: A System for Large-Scale Machine Learning, in Proceedings of the 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI '16), pp. 265–284., 2016.

Belloni, F. F., Keskes, N. and Hurford, A. J.: Strategy for fission-track recognition via digital image processing, and computer assisted track measurement, in 9th International Conference on Fission-Track Dating and Thermochronology: Geological
 Society of Australia Abstracts, pp. 15–17., 2000.

Bradski, G.: The OpenCV Library, Dr Dobbs J. Softw. Tools, 25, 120-125, doi:10.1111/0023-8333.50.s1.10, 2000.

Collobert, R., Bengio, S. and Maréthoz, J.: Torch: a modular machine learning software library, IDIAP Res. Rep., 02–46, 2002.

500 Donelick, R. A.: Apatite etching characteristics versus chemical composition, Nucl. Tracks Radiat. Meas., 21.604, 1359–0189,

Verwijderd: ¶

### 1993.

Enkelmann, E., Ehlers, T. A., Buck, G. and Schatz, A. K.: Advantages and challenges of automated apatite fission track counting, Chem. Geol., 322–323, 278–289, doi:10.1016/j.chemgeo.2012.07.013, 2012.

505 Fleischer, R. L., Price, P. B. and Walker, R. M.: Nuclear tracks in solids: principles and applications, University of California Press., 1975.

Gleadow, A. J. W., Duddy, I. R., Green, P. F. and Lovering, J. F.: Confined fission track lengths in apatite: a diagnostic tool for thermal history analysis, Contrib. to Mineral. Petrol., 94(4), 405–415, doi:10.1007/BF00376334, 1986.

Gleadow, A. J. W., Gleadow, S. J., Belton, D. X., Kohn, B. P., Krochmal, M. S. and Brown, R. W.: Coincidence mapping - A
key strategy for the automatic counting of fission tracks in natural minerals, Geol. Soc. London, Spec. Publ., 324(1), 25–36, doi:10.1144/SP324.2, 2009.

Gold, R., Roberts, J. H., Preston, C. C., Mcneece, J. P. and Ruddy, F. H.: The status of automated nuclear scanning systems, Nucl. Tracks Radiat. Meas., 8, 187–197, 1984.

Green, P. F., Duddyi, I. R., Gleadow, A. J. W., Tingate, P. R. and Laslett, G. M.: Thermal annealing of fission tracks in apatite 1. A Qualitative description, Chem. Geol., 59, 237–253, 1986.

Hurford, A. J. and Green, P. F.: The zeta age calibration of fission-track dating, Chem. Geol., 41, 285–317, doi:10.1016/S0009-2541(83)80026-6, 1983.

Jia, Y., Shelhamer, E., Donahue, J., Karayev, S., Long, J., Girshick, R., Guadarrama, S. and Darrell, T.: Caffe: Convolutional Architecture for Fast Feature Embedding, Proc. 22nd ACM Int. Conf. Multimed., 675–678, doi:10.1145/2647868.2654889, 2014.

Jonckheere, R.: On the densities of etchable fission tracks in a mineral and co-irradiated external detector with reference to fission-track dating of minerals, Chem. Geol., 41–58, doi:10.1016/S0009-2541(03)00116-5, 2003.

Kumar, R.: Machine learning applied to autonomous identification of fission tracks in apatite, Goldschmidt2015 Abstr., 1712, 2015.

525 Lundh, F.: An Introduction to Tkinter, Rev. Lit. Arts Am., (c), 166, 1999.

Malusà, M. G. and Fitzgerald, P.: Fission-Track Thermochronology and its Application to Geology, edited by M. G. Malusà and P. Fitzgerald, Springer International Publishing., 2019.

Petford, N., Miller, J. A. and Briggs, J.: The automated counting of fission tracks in an external detector by image analysis, Comput. Geosci., 19(4), 585–591, 1993.

530 Van Ranst, G., Baert, P., Fernandes, A. C. and De Grave, J.: Technical note: Nikon – TRACKFlow, a new versatile microscope

Verwijderd: ¶

515

system for fission track analysis, Geochronology, 2(1), 93-99, 2020.

535

Redmon, J. and Farhadi, A.: YOLOv3: An Incremental Improvement, ArXiv [online] Available from: http://arxiv.org/abs/1804.02767, 2018.

Redmon, J., Divvala, S., Girshick, R. and Farhadi, A.: You Only Look Once: Unified, Real-Time Object Detection, Proc. IEEE Conf. Comput. Vis. pattern Recognit., 779–788, 2016.

Van Rossum, G. and Drake Jr, F. L .: Python reference manual, Amsterdam., 1995.

Schindelin, J., Arganda-Carreras, I., Frise, E., Kaynig, V., Longair, M., Pietzsch, T., Preibisch, S., Rueden, C., Saalfeld, S., Schmid, B., Tinevez, J. Y., White, D. J., Hartenstein, V., Eliceiri, K., Tomancak, P. and Cardona, A.: Fiji: An open-source platform for biological-image analysis, Nat. Methods, 9(7), 676–682, doi:10.1038/nmeth.2019, 2012.

540 de Siqueira, A. F., Nakasuga, W. M., Guedes, S. and Ratschbacher, L.: Segmentation of nearly isotropic overlapped tracks in photomicrographs using successive erosions as watershed markers, Microsc. Res. Tech., 82(10), 1706–1719, doi:10.1002/jemt.23336, 2019.

Wagner, G. A.: Archaeological applications of fission-track dating, Nucl. Track Detect., 2(1), 51–63, doi:10.1016/0145-224X(78)90005-4, 1978.

545 Wagner, G. A.: Fission-track ages and their geological interpretation, Nucl. Tracks, 5(1–2), 15–25, doi:10.1016/0191-278X(81)90022-6, 1981.

Wagner, G. A. and Van den haute, P.: Fission-Track dating, Kluwer Academic Publishers, Dordrecht., 1992.

# 550 Figures

# Al-Track-tive

# \* How to install?

- download Al-Track-tive project on
- https://github.com/SimonNachtergaele
- follow instructions for Windows, Mac-OS or Linux
- open .exe file or run Python code in Python code editor
- \* Determines track density in apatite/mica (tutorial available) • load .weights file (DNN for apatite) from **option A or B**
- load .weights file (DNN for mica) obtained in option A or B
- load Yolov3 configuration file (.cfg)
- select reflected light and transmitted light images of apatite and/or ED
- select Region Of Interest: square, custom polygon or circle
- manual check of the automatic track identification results
- \* Live fission track recognition (tutorial available)
- \* Etch pit diameter (Dpar) measurement (tutorial available)
- free to download on https://github.com/SimonNachtergaele

   Option B: Make your own Deep Neural Network

   \* Create training dataset using Labeling
   • download Labeling on https://github.com/tzutalin/labeling
   • annotate tracks in 50 apatite images
   • annotate tracks in 50 external detector images

**Option A: Use our Deep Neural Networks** 

# \* Execute Jupyter notebook in Google Colab

- download Jupyter notebook (.ipynb) on
- https://github.com/SimonNachtergaele
- connect to Google Colab
- iterate
- download .weights file from Google Drive



Figure 1: Visual representation of the presented AI-Track-tive software and its functionalities



Verwijderd: ¶ Figure 1: Flow chart of



Figure 2: frequency histograms illustrating the areal track density of the training datasets. The horizontal axis expresses the 10-based log of the areal track density of the training dataset.



560

Figure 3: fission track recognition in muscovite (external detector). Blue squares indicate automatically recognized semi-tracks. The percentage displayed above every blue box indicates the confidence score for that particular group of pixels to be recognized as semi-track. The small fraction of unrecognized tracks ("false negatives") is manually indicated with green squares. Red squares indicate erroneously indicated tracks ("false positives"). The two track bars above the image indicate the possibility to compare different focal levels or change between reflected and transmitted light,

Verwijderd: AI-Track-tive ¶



Figure 2: fission track recognition results in apatite (scale: image is 100  $\mu$ m on 100  $\mu$ m) of Al-Track-tive. Panel A shows a pre-annealed Durango apatite (A-DUR) in which 23 out of 29 tracks were found automatically (success rate = 79%). Panel B shows a sample with a track density of  $1.26 * 10^6 tracks/cm^2$  in which only 43 out of 59 tracks (73% success rate) were found and 1 was mistakenly added by the computer vision track identifier. Panel A and B show a custom-chosen polygonal counting window and panel C shows a circular window of 80  $\mu$ m diameter on a Durango apatite in which all tracks were found automatically. ¶



Verwijderd: ¶ Figure 3:

- Verwijderd:
- Verwijderd: ¶



Figure 4: example of semi-automatic Dpar measurement result obtained on a part of an image taken on 1000x magnification. The green ellipses are the remainders from a segmentation process. The values written next to the ellipses stand for length in µm (black), elongation factor (red) and angle (blue). Some green ellipses show no values because they have been excluded by the elongation filter, direction filter, minimum size filter or maximum size filter.



Figure 5-Performance metrics of the deep neural networks obtained on a dataset containing 50 "test images". The precision (true positives/(true positives/(true positives/)) and recall (true positives/(true positives + false negatives)) of the automatic fission track recognition deep neural network are shown for apatite and muscovite mica (external detector). The 10-based log of areal track density (tracks/cm<sup>2</sup>) is shown on the horizontal axis of the upper scatter plots. The frequency-histograms below show the distribution of the performance metrics.



585

#### Tables

610

# Verwijderd: ¶

Apatite sample

Y Table 1: test results of the automatic fission track recognition in apatite (confidence threshold = 0.1). Areal track density is expressed in tracks/cm<sup>2</sup>. The number of correctly automatically detected tracks (True Positives), manually detected tracks (False Negatives) and erroneously detected tracks (False Positives) are indicated by n<sub>auto</sub> and n<sub>manual</sub> and n<sub>auto false</sub>, respectively.

Testing	Area (µm²)	Track density	<u>Total</u>	n auto	n manual	n auto false	precision	recall
BC-04 X12	10000	9.10E+05	<u>91</u>	80	13	2	98%	86%
BC-04 X16	10000	2.73E+06	273	225	51	3	99%	82%
BC-04 X18	10000	3.62E+06	362	271	<u>92</u>	1	100%	75%
BC-04 X19	10000	1.73E+06	173	150	23	<u>0</u>	100%	<u>87%</u>
BC-04 X21	4280	1.21E+06	52	36	<u>16</u>	<u>0</u>	100%	69%
BC-04 X24	2745	1.46E+06	40	27	<u>13</u>	<u>0</u>	100%	68%
DUR-G2 X21	10000	1.50E+05	15	12	3	0	100%	80%
DUR-G2 X22	10000	2.00E+05	20	18	2	0	100%	90%
DUR-G2 X23	10000	2.00E+05	20	16	4	0	100%	80%
DUR-G2 X24	10000	2.30E+05	23	21	2	0	100%	91%
DUR-G2 X25	10000	1.70E+05	17	11	6	0	100%	65%
DUR-G2 X26	10000	1.70E+05	17	14	3	0	100%	82%
DUR-G2 X27	10000	2.00E+05	20	13	7	0	100%	65%
DUR-G2 X28	10000	2.00E+05	20	17	3	0	100%	85%
DUR-G2 X29	10000	2.10E+05	21	13	8	0	100%	62%
DUR-G2 X30	10000	2.60E+05	26	22	4	0	100%	85%
DUR-G2 X31	10000	2.20E+05	22	20	2	<u> </u>	100%	91%
DUR-G2 X32	10000	9.00F+04	9	8	1	0	100%	89%
DUR-G2 X33	10000	1.90E+05	19	11	*	0	100%	58%
DUR-G2 X35	10000	2 50E+05	25	20	5	0	100%	80%
DUR-G2 X41	10000	1.60E+05	16	14	3	<u> </u>	93%	82%
E115 X03	10000	1 98F+06	198	170	28	1	99%	86%
F115 X04	10000	1 73E+06	173	149	24	Ê	100%	86%
F115 X05	10000	1 28E+06	128	105	23	0	100%	82%
F115 X07	10000	1.63E+06	163	147	17	1	99%	90%
F115 X08	10000	1.99F+06	199	186	14	÷ 1	99%	93%
F115 X09	10000	1.68E+06	168	147	22	- 1	99%	87%
F115 X10	10000	1.51E+06	151	130	21	÷.	100%	86%
BC-04 X3	10000	7.00E+05	70	64	6	<u> </u>	100%	91%
BC-04 X6	10000	1.52E+06	152	120	32	<u> </u>	100%	79%
BC-04 X7	10000	2.00E+06	200	162	38	<u> </u>	100%	<u>73%</u> 81%
BC-04 x14	10000	8 80E+05	88	89	7	<u>×</u>	92%	93%
BC-04 X17	10000	1.02E+06	102	91	13	2	98%	88%
BC-04 X20	10000	1.80E+05	18	26	2	10	72%	93%
BC-04 X20	10000	2.60E+06	260	20	24	10	100%	01%
A-DUR-G1 V21	10000	4.60E±05	205	45	24	2	96%	0/%
A-DUR-G1 X21	10000	3 40E+05	34	22	2	<u></u>	100%	0/1%
A-DUR-G1 X22	10000	4 30E±05	<u>34</u> /2	40	2	1	08%	02%
A-DUR-G1 X24	10000	3 70F+05	37	40	2	± 5	<u>36%</u> 89%	100%
A-DUR-G1 X24	10000	3.70E+05	<u>37</u> 48	<u>42</u> 52	1	2	03/0	0.00%
A-DUR-G1 X25	10000	4.00E+05	40	<u>33</u> 42	1	<u>0</u>	<u>90%</u>	<u>30%</u>
A-DUR-G1 X20	10000	3 80E±0E	20	43	1	4 10	<u>31/0</u> 830/	100%
	10000	3.80E+05	<u>30</u>	48 57	0	10	0.0%	100%
	10000	3.30E+05	23	<u>55</u>	4	<u>b</u>	<u>90%</u>	<u>93%</u>
A DUR C1 V20	10000	4.70E+05	47	<u>52</u>	1 2	<u>b</u>	<u>90%</u>	<u>98%</u>
A DUD C1 V21	10000	4.50E+05	40	48	3	<u>b</u>	<u>89%</u>	<u>94%</u>
	10000	4.00E+05	<u>40</u> 20	40	<u>2</u>	<u>2</u>	<u>95%</u>	<u>95%</u>
A-DUR-G1 X32	10000	3.80E+05	<u>38</u>	40	0	<u>2</u>	<u>95%</u>	100%
A-DUR-G1 X33	10000	4.30E+05	43	3/	<u>6</u>	<u>0</u>	100%	86%
A-DUR-G1 X34	10000	4.90E+05	49	4/	2	0	100%	96%
A-DUR-G1 X35	10000	3.90E+05	39	44	<u>1</u>	<u>6</u>	88%	98%
A-DUK-G1 X30	10000	5.00E+05	50	48	<u>3</u>	1	98%	94%
Arithmetic mean							97%	86%

Verwijderd: Table 1: results of the automatic fission track recognition in apatite. Areal track density (p) is expressed in tracks/cm<sup>2</sup>. The number of automatically and manually detected tracks is indicated by n<sub>atot</sub> and n<sub>manual</sub>, respectively.¶

....

Table 2: test results of the automatic fission track recognition in muscovite mica (confidence threshold = 0.3). Areal track density is expressed in tracks/cm<sup>2</sup>. The number of correctly automatically detected tracks (True Positives), manually detected tracks (False Negatives) and erroneously detected tracks (False Positives) are indicated by n<sub>auto</sub> and n<sub>manual</sub> and n<sub>auto false</sub>, respectively.

Testing	<u>Area</u> (μm²)	Track density	<u>Total</u>	<u>n <sub>auto</sub></u>	<u>n <sub>manual</sub></u>	<u>n auto false</u>	precision	<u>recall</u>
<u>GL 16 X31</u>	<u>10000</u>	5.20E+05	<u>52</u>	<u>47</u>	<u>5</u>	<u>0</u>	<u>100%</u>	90%
GL 16 X32	10000	3.60E+05	<u>36</u>	33	4	<u>1</u>	<u>97%</u>	89%
<u>GL 16 X33</u>	10000	5.30E+05	53	48	<u>7</u>	<u>2</u>	<u>96%</u>	<u>87%</u>
<u>GL 16 X34</u>	10000	4.50E+05	45	33	<u>12</u>	<u>0</u>	<u>100%</u>	<u>73%</u>
GL 16 X35	10000	5.10E+05	<u>51</u>	48	<u>5</u>	<u>2</u>	<u>96%</u>	<u>91%</u>
GL 16 X36	10000	4.00E+05	<u>40</u>	<u>36</u>	<u>4</u>	<u>0</u>	<u>100%</u>	<u>90%</u>
GL 16 X37	10000	4.70E+05	47	36	<u>11</u>	<u>0</u>	<u>100%</u>	77%
GL 16 X38	10000	3.90E+05	39	34	6	1	<u>97%</u>	85%
GL 16 X39	10000	4.20E+05	42	36	8	2	95%	82%
GL 16 X40	10000	5.90E+05	59	60	5	6	91%	92%
GL 16 X41	10000	3.90E+05	39	34	5	0	100%	87%
GL 16 X42	10000	6.10E+05	61	60	2	1	98%	97%
GL 16 X43	10000	4.40E+05	44	35	9	0	100%	80%
GL 16 X44	10000	4.10E+05	41	35	6	0	100%	85%
GL 16 X45	10000	5.40E+05	54	47	8	1	98%	85%
GL 16 X46	10000	5 10E+05	51	48	5	2	96%	91%
GL 16 X47	10000	4 20E+05	42	35	7	0	100%	83%
E115 X28	10000	1 48F+06	148	145	6	3	98%	96%
F115 X29	10000	1.61E+06	161	148	15	2	99%	91%
E115 X20	10000	7.0000	70	77	2	<u>~</u> 1	00%	96%
E115 X21	10000	1 17E±06	117	112	5	± 2	08%	05%
E115 X31	10000	1.172+00	141	115	<u>0</u>	2	<u>56%</u>	<u>93%</u>
F115 X32	10000	1.410-00	141	140	<u>0</u>	2	<u>33/0</u>	93/0
F115 X35	10000	1.13E+00	113	90	10	2	<u>97%</u>	05%
F115 X34	10000	8.00E+05	202	102	4	<u>v</u>	100%	95%
F115 X35	10000	<u>2.02E+00</u>	202	193	14	2	97%	93%
F115 X30	10000	0.80E+05	125	110	<u> </u>	<u> </u>	<u>97%</u>	97%
F115 X37	10000	1.25E+00	125	110	<u>/</u>	<u>v</u>	100%	94%
F115 X36	10000	1.280+00	128	120	<u>/</u>	2	90%	95%
F115 X39	10000	5.60E+05	50	53	4	<u>+</u>	98%	93%
F115 X40	10000	1.1/E+06	11/	111	8	<u> </u>	98%	93%
FCTG4 X31	10000	5.00E+05	50	50	1	<u>+</u>	98%	98%
FCTG4 X32	10000	5.00E+05	50	45	<u>6</u>	<u>+</u>	98%	88%
FCTG4 X34	10000	6.30E+05	63	63	1	1	98%	98%
FCTG4 X35	10000	6.10E+05	<u>61</u>	58	4	1	98%	<u>94%</u>
FCTG4 X36	10000	3.60E+05	36	42	3	9	82%	<u>93%</u>
FCTG4 X37	<u>10000</u>	<u>1.90E+05</u>	<u>19</u>	<u>16</u>	<u>3</u>	<u>0</u>	100%	84%
FCTG4 X38	<u>10000</u>	5.80E+05	<u>58</u>	<u>54</u>	<u>6</u>	<u>2</u>	96%	<u>90%</u>
FCTG4 X39	<u>10000</u>	5.20E+05	<u>52</u>	54	<u>3</u>	<u>5</u>	<u>92%</u>	<u>95%</u>
FCTG4 X40	<u>10000</u>	<u>3.10E+05</u>	<u>31</u>	<u>26</u>	<u>5</u>	<u>0</u>	<u>100%</u>	84%
FCTG4 X41	<u>10000</u>	4.30E+05	43	<u>39</u>	<u>4</u>	<u>0</u>	<u>100%</u>	<u>91%</u>
ADURG1x1	10000	3.00E+05	<u>30</u>	<u>28</u>	<u>2</u>	<u>0</u>	<u>100%</u>	<u>93%</u>
ADURG1x2	10000	4.80E+05	<u>48</u>	45	<u>3</u>	<u>0</u>	<u>100%</u>	94%
ADURG1x3	10000	4.30E+05	<u>43</u>	<u>48</u>	<u>2</u>	<u>7</u>	<u>87%</u>	<u>96%</u>
ADURG1x4	10000	4.90E+05	<u>49</u>	<u>49</u>	<u>1</u>	<u>1</u>	<u>98%</u>	<u>98%</u>
ADURG1x5	10000	3.60E+05	<u>36</u>	<u>32</u>	5	<u>1</u>	<u>97%</u>	<u>86%</u>
ADURG1x6	10000	4.60E+05	<u>46</u>	<u>46</u>	<u>1</u>	<u>1</u>	<u>98%</u>	<u>98%</u>
ADURG1x7	10000	4.80E+05	48	48	<u>1</u>	<u>1</u>	<u>98%</u>	<u>98%</u>
ADURG1x8	10000	5.70E+05	<u>57</u>	<u>56</u>	<u>1</u>	<u>0</u>	<u>100%</u>	<u>98%</u>
ADURG1x9	10000	2.90E+05	29	26	<u>3</u>	<u>0</u>	<u>100%</u>	<u>90%</u>
ADURG1x10	10000	3.30E+05	<u>33</u>	<u>32</u>	<u>1</u>	<u>0</u>	<u>100%</u>	<u>97%</u>
Arithmetic mean							98%	<u>91%</u>

#### Verwijderd: ¶ ¶

¶

 

 Table 2: results of the automatic fission track recognition in muscovite (external detector). Areal track density (p) is expressed in tracks/cm<sup>2</sup>. The number of automatically and manually detected tracks is indicated by n<sub>auto</sub> and n<sub>manuab</sub> respectively.¶ Muscovite sample

Table 3: estimated time for 20-30 grains/polygons using different automated track recognition software packages and manual counting results from Enkelmann et al. (2012). Non-specified information is indicated with ns.

	Туре	Alignment (min)	Grain selection + imaging (min)	Counting (min)	Analysis/comput er conversion (min)	Total time (min)
	Analyst 1 FastTracks (Enkelmann et al. 2012)	20	40-60	180-240	40-90	240-410
Enkelmann et	Analyst 2 FastTracks (Enkelmann et al. 2012)	20-30	30-60	120-240	90-180	260-510
al. (2012)	Manual (sandwich technique, analyst 1) Manual (sandwich technique, analyst 2)	10		30-45	20 (digitizing data)	60-75
		5-15		30-90	20 (digitizing data)	55-125
<u>A. Gleadow</u> (pers. com. <u>2020)</u>	FastTracks 2020	<u>ns</u>	<u>15-17</u>	<u>10-20</u>	<u>ns</u>	<u>ns</u>
This paper	AI-Track-tive (Durango sample)	10-20	25-35	30	5	70-90

Verwijderd: ¶

Verwijderd: 3

Verwijderd: ¶